

LPW2

Power ranges: 6.8 - 14.7 kW; 9.1 - 19.7 bhp
Variable speed; full load speed range: 1500 - 3000 r/min
Durable, reliable, easy to maintain liquid cooled diesel engines

Power Outputs

Power	r/min	1500	1800	2000
Continuous	kW	6.8	8.5	9.6
	bhp	9.1	11.4	12.9
Fuel Stop	kW	7.5	9.4	10.6
	bhp	10	12.6	14.2

Special Attributes

- variable and fixed speed builds available
- 500 hour service intervals
- designed for continuous operation in ambient temperatures up to 52°C (122°F)
- cold start capability down to -32°C (-25.6°F)

Basic Engine Characteristics

- diesel fuelled
- direct injection
- 2 cylinders
- liquid cooled
- naturally aspirated

Design Features and Equipment

- heavy duty air cleaner
- inlet and exhaust manifolds
- inlet manifold heater plugs
- fuel lift pump
- self-vent fuel system with individual fuel injection pumps
- fuel filter/agglomerator
- gear-driven positive displacement type lubricating oil pump
- spin-on lubricating oil filter
- 12V electric start
- flywheel with ring gear **
- SAE 5 flywheel housing
- operators' handbook
- deep sump (3600r/min only)

Emissions

- models under 19 kW comply with EU Stage 3A exhaust emissions regulations

Optional Items

- low oil pressure switch
- radiator options with choice of pusher or puller fan and full guarding
- extended warranty