DIESEL AND GAS GENERATING SETS

Power outputs are to ISO 8528
Voltage (50Hz)
single phase: 220-230-240 V
three-phase: 380/220, 400/230, 415/240 V
Power Factor: single-phase: 1.0 pf; three-phase:0.8 pf.

Genset Rating Definitions to ISO 8528-1
Operating Conditions: A standard generating set is designed to operate in environmental conditions not exceeding an air inlet temperature of 25 C (77 F), altitude (above sea level) 152.4 metres (500 feet) and a relative humidity of 60%.
Prime Power: This rating is for the supply of continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation on the annual hours of operation and 10% overload power can be supplied for 1 hour in 12 hours.
Standby Power: This rating is for the supply of continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted.

50 Hz

DIESEL | GAS

AIR COOLED | LIQUID COOLED

LISTER PACK

AD1

HSL OPEN SET

HSL AND LLD (ALPHA) ACOUSTIC SET

LLD (ALPHA) OPEN SETS

DELTA ACOUSTIC SET

GAMMA ACOUSTIC SET

LLO (OMEGA) OPEN SET

GS (ALPHA) GAS GENSET

| Genset Type | | | | Engine series | K Series | | AD | T Series | | | | | | Alpha Series | | | | | |